

Report BS 5867-2 type B

Doc number:

Customer:

Quality name: RE-Juvenate 03-Improved Report date:

Place analyses:

Date test request:

Samples received:

27/02/2020

(beige) (DEV1 BAAF)

27/02/2020 Date analyses:

VEROTEX Industries

202000563

Edisonweg 3 5466 AR Veghel

Labotex

Netherlands

14/02/2020 14/02/2020

Testing and conditioning in standard atmosphere, T (20+/-2)°C and RH (65+/-4)%

Specification	Results							Remarks	1
Burning behaviour of fabrics for curtains drapes	1. Test on original fabric								
Based on 35 5867, part 2		fa ce	warp face	reverse	face	weft	reverse		
conditioning min 24h. in standard atmosphere sample size: (220 x 170) mm used gas: propane flame height: 40 mm flame application: 15 s surface igntion	afterflame time (s)	0.0	0.0	0.0	0.0	0.0	0.0	5. C. S.	
	afterglow time (s)	0.0	0.0	0.0	0.0	0.0	0.0		
	edge reached	no	no	no	no	no	no	**************************************	
Method test for:	burning debris	no	no	no	no	no	no		
Flame spread: BS EN ISO 15025 Laundering: BS EN ISO 10528	2. Test on wasned fabric								
	v/arp weft								
		fa ce	face	reverse	face	face	reverse		
	afterflame time (s)	0.0	0.0	0.0	0.0	0.0	0.0		
	afterglow time (s)	0.0	0.0	0.0	0.0	0.0	0.0		
	edge reached	no	no	no	no	no	no		
	burning debris	no	no	no	no	no	no		
	3, Acceptance criteria No part of any hole nor any part of the lowest boundary of any flame shall reach the top edge or either vertical edge of sample. If so and if there is no separation of any flaming debris droplets, the fabric shall be deemed to comply with the requirements of this standard.								
E LAC 364-YEST	4. Conclusion The fabric's flammability complies with the requirements of BSS867-2 type B.								

ANA00020 Page 1 of 2

Version: 13.0 Approval date: 15/05/2017



Report BS 5867-2 type B

Doc number:

202000563

Report date: 27/02/2020

Date analyses:

Date test request:

Samples received:

Quality name:

RE-Juvenate 03-Improved

27/02/2020

(beige) (DEV1 BAAF)

Place analyses:

VEROTEX Industries Customer: Edisonweg 3

14/02/2020

5466 AR Veghel Netherlands

Labotex

14/02/2020

Labotex certifies that the results mentioned in this report are obtained after testing in accordance with the procedure and equipment specified by the concerned standards, unless noted differently.

Joeri Neys - Laboratory Manager

Labotex has the competence to perform tests in accordance with the requirements of standard NBN EN ISO/IEC 17025. The scope of this accreditation can be obtained on request. The results in this report only relate to the tested items.

mples will be returned to the customer with the certificate, if possible. Samples will not be retained, unless specified by the customer. Retained samples will be kept for maximum one ye unless a specific retention period is necessary.

This report can not be copied unless in its complete form and with written approval of Labotex (Kontich).

Sampling is performed by the costumer. Fabric analysed as received.

The uncertainty and the description of the methods are available at the lab on request.

ANA00020 Page 2 of 2

Version: 13.0 Approval date: 15/05/2017